



# AUSTRALIAN TECHNOLOGY MANAGEMENT

## ATM Industry Solutions



### Basic Model ATM Alarm - *Over 5000 units sold since 2005.*

#### How does the ATM Alarm work?

The ATM Alarm is activated by detecting motion, degree of tilt, light and/or contact switch. The alarm, once activated, will produce an ear piercing 120db siren for 10 hours, or until turned off or reset by keyed switch.

If the ATM is moved the alarm is activated.



If the ATM is tilted the alarm is activated.



#### AUSTRALIAN TECHNOLOGY MANAGEMENT

P.O Box 888 Marrickville 1475  
Sydney NSW AUSTRALIA

[www.atmgroup.net.au](http://www.atmgroup.net.au)

Phone: +61 2 9569 7007

Fax: +61 2 8569 0162

[info@atmgroup.net.au](mailto:info@atmgroup.net.au)



**If the ATM is cut into with a torch, saw, grinder or axe, the alarm is activated.**



**If the ATM is pried into the alarm is activated.**



**No false alarms.**

**Mild bumps won't activate the alarm.**



The ATM Alarm cannot be disabled or produce a false alarm from outside the ATM from power outages or unplugging the power cord.

#### AUSTRALIAN TECHNOLOGY MANAGEMENT

P.O Box 888 Marrickville 1475  
Sydney NSW AUSTRALIA

[www.atmgroup.net.au](http://www.atmgroup.net.au)

Phone: +61 2 9569 7007  
Fax: +61 2 8569 0162

[info@atmgroup.net.au](mailto:info@atmgroup.net.au)



## Features

- Inexpensive
- Basic installation is less than 30 minutes
- Activated by: motion / tilt / light / shock / contact switch
- Two 120 db sirens
- Keyed switch (on/off/reset) (on multiple orders, alarms can be keyed the same)
- External keyed switch (optional)
- Door contact switches (optional)
- External siren (optional)
- Shock Sensor w/16" closed loop wire (optional)
- External Blinking LED (optional)
- Adjustable light sensor (off/min/max)
- Two LED lights (alarm on/battery charger on)
- Siren Time Switch (adjustable: 30 sec/5 min/30 min/auto) (siren times can be changed for custom orders)
- Trickle cell battery charger
- 6 volt rechargeable battery (power outages do not disable the alarm)
- Battery replacement indicator (sounds a chirp every two minutes) (expected battery life 5 to 7 years)
- Small in size (9"x 6"x 3" and weighs less than 4lbs)
- Can be added to any existing building alarm systems
- Helps protect ATM from line surges
- Lowers insurance costs
- 1 year limited warranty



[Contact us.](#) Comprehensive ATM alarm systems engineered to all requirements.

### AUSTRALIAN TECHNOLOGY MANAGEMENT

P.O Box 888 Marrickville 1475 Phone: +61 2 9569 7007  
Sydney NSW AUSTRALIA Fax: +61 2 8569 0162  
www.atmgroup.net.au info@atmgroup.net.au

